

DS-PS1-II-WB



The wireless internal sounder DS-PS1-II-WB, supporting 433MHz two-way communication via Cam-X protocol, multiple alarm sounds, strobe light indication, is used for instant alerting when alarm triggered. Meanwhile, it supports two-way audio function for ARCs to do the alarm verification, which can help the users to know what is the real situation on-site immediately.

- 433 MHz two-way wireless communication
- Configurable arming/disarming prompt sound and LED indicator
- Two-way talk via RF transmission
- Buzzer Decibel: 90 to 110 dB
- Long battery life span
- 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design

▪ Specification

Hardware features	
Serial port	1
Tamper-Proof	Supported, front and rear
Buzzer	Supported
Power switch	Power on/off
Mic	Supported
Electrical characteristics	
Operation humidity	10% to 90% (no condensing)
Operation temperature	-10°C~55°C
Battery type	Four CR123 batteries
Power supply	Support 12VDC Power Supply
Power interface	12VDC
Power consumption	Quiescent current: 25 uA Max current: 1.6 A Voltage: 3 V
Battery life span	Up to 2 years (standby time)
Wireless transmission	
RF frequency	433 MHz
RF modulation	2GFSK
RF distance	800m (open area)
Wireless technology	CAM-X Wireless Technology
Display	
LED Indicator	Enrollment/Signal (red/green), Alarm(Blue/Red), Two-way audio service(Blue/Red)
General	
Dimension(WxHxD)	130 × 128 × 39.5 mm
Installation method	Wall mounting
Color	White Case (Blue or Red LED Alarm)
Weight	361.0 g

▪ Available Model

DS-PS1-II-WB

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

